

## PNEUMATIC TAPPING TOOL



**STH-12A**  
Pneumatic Various degree Tapping Hand Tool



**STH-12B**  
Pneumatic Chuck Tapping Hand Tool



**STH-12C**  
Pneumatic Torsional Tapping Hand Tool


### Specifications :

Model No.	For Tap	Speed (r.p.m.)	Spindle Type	Max. Air Consumption (Nm <sup>3</sup> / min)	Air Hose Size (min)	Weight(kg)	Parts
STH-12A	M2~M12	250	HTP/B12	0.4	9.5	2.5	Wrench
STH-12B	M2~M12	250	CAP10/B12	0.4	9.5	2.5	Wrench
STH-12C	M2~M12	250	TH1/B12	0.4	9.5	4	W/6pcs Torsional Collets+Wrench

## ACCESSORIES OF TAPPING MACHINE

### Adaptor Type STC-1E~4E

With safty clutch




Model No.	For Tap	Suitable Adaptors Size	D	D1	D2	L1	L3	L4	L5	Weight (kg)	Suitable Model
STC-1E	M2~M14	1	32	19	19	71	25	21.5	25	0.15	8,12 series
STC-2E	M6~M27	2	50	30	31	30	31	35	33	0.55	16~27 series
STC-3E	M16~M42	3	72	47	48	44	41	55.5	50	1.70	For Hydraulic
STC-4E	M22~M50	4	95	60	60	33	16	63	73	3.30	For Hydraulic

\* TAP shank Dimension for JIS,DIN,ISO,ANSI(USA),please specify

### Adaptor Type STR

For reducing



Model No.	Suitable Adaptors Size	for Adaptors Size	D	D1	D2	L1	L3	Weight (kg)
STR-21	2	1	48	19	31	5	35	0.17
STR-32	3	2	70	31	48	6	55.5	0.60
STR-43	4	3	92	48	60	13	63	1.00

### Drill Chuck Collet



Model No.	For Drill Chuck	Capacity (mm)	D	D1	D2	L1	Weight (kg)
STC-JT2A	8H	0 - 8	30	13.94	19	31	0.06
STC-JT6A	13H	0 - 12	30	17.17	19	34	0.06
STC-JT6B	13H	0 - 12	48	17.17	31	37	0.3

### Drill Chuck



Model No.	Capacity		Taper Mount No. Din or Jacobs	Length(m/m)		Weight (kg)	Outer Dia(m/m)	N.W/GW (kg)
	mm	inch		Open	Closed			
STC-8H	0~8	0~5/16	JT2	68	76	0.395	38	16/17
STC-13H	0~13	0~1/2	JT6	90	102	0.92	48	23/24

## SUMAKE Industrial Co., Ltd.

4F, No.351, Yangguang St., Neihu District, Taipei, Taiwan, Zip:114-91

Tel: 886-2-2659-3500

Fax: 886-2-2659-3700

http://www.sumake.com

e-mail: sales@sumake.com.tw



Certificate TW04/02301

0812181-C

PAGE02